



Optimuz RP80 Thermal Receipt Printer - 3 interface - USB+RS232+Ethernet Port

Color		Black
Print	Printing Method	Thermal Line
	Printing Speed	230mm/s
	Resolution	8 dots/mm, 576 dots/line
	Effective Printing Width	72mm
Character	Character Set	ANK,GB18030(Chinese)
	Print Font	ANK: 12 x24 Chinese: 24 x 24
	Character per Line	42
Paper Spec	Paper Type	Thermal paper
	Paper Width	79.5± 0.5mm
	Paper Roll Diameter	Max: 80.0mm
	Roll Core Inner Diameter	13mm(min.)
	Paper Thickness	0.06 to 0.07mm
Paper Supply Method		Drop-in paper load
Reliability	MCBF	60 million lines
	Auto Cutter	500,000 cuts
	TPH	100km
Barcodes	UPC-A,UPC-C,EAN-13,EAN-8,CODE39,ITF,CODEBAR,CODE93,CODE128	
Emulation		ESC/POS
Driver		Windows2000/XP /7 32,64 bit /VISTA/Win8 32,64bit
Sensor		Paper Near End Sensor, Paper End Sensor
Drawer Port		1 Port
Interface		RS-232 + USB + Ethernet
Power Supply (Adapter)		AC100 ~240V(± 10%) DC 24V, 2A
Auto cutter	Type	Guillotine
	Life	1,000,000 cuts
Net Weight		1.6kg

Physical	Gross Weight	2.8kg
	Printer Dimension (WxLxH)	145 x 195x 148 mm
Application	Restaurants, Department Stores, Kitchen, Convenience Stores, Specialty Retail, Super market	